




211040
OGUL 031 G3-T3
Laser fork light barrier

- Light/dark switching
- IO-Link
- 4 operating modes as an IO-Link parameter
- Switch-on/off delay as an IO-Link parameter
- Diagnostics with IO-Link
- Metal casing
- Electronics integrated
- High switching frequency
- Bright ring LED
- High protection type



Function														

Technical data (typ.)	+20°C, 24 V DC
Service voltage	10 ... 30 V DC
No-load current (max.)	30 mA
Insulation voltage endurance	500 V
Leg length internal	35 mm
Housing dimensions	50 x 60 x 10 mm
Housing length	60 mm
Housing height	50 mm
Housing width	10 mm
Housing material	Die-cast zinc (Black, powder-coated)
Weight	68 g
Protection class	III, operation on protective low voltage
Operating principle	Optical
Evaluation	digital
Design	Fork
Operation modes	STANDARD, HIGH RESOLUTION, POWER, SPEED
Switching output	Push-pull/PNP/NPN, 100 mA, NO/NC
Voltage drop (max.)	1 V
Interface	IO-Link
Light source	Laser
Laser class	1 (IEC 60825-1)
Color	red
Modulation	Clocked
Fork opening	30 mm



211040
OGUL 031 G3-T3
Laser fork light barrier

Technical data (typ.)	+20°C, 24 V DC
Resolution (factory setting)	0,05 mm (STANDARD)
Reproducibility (factory setting)	0,01 mm (STANDARD)
Resolution (STANDARD)	0,05 mm
Reproducibility (STANDARD)	0,01 mm
Resolution (HIGH RESOLUTION)	0,03 mm
Reproducibility (HIGH RESOLUTION)	0,01 mm
Resolution (POWER)	0,1 mm
Reproducibility (POWER)	0.015 mm
Resolution (SPEED)	0,05 mm
Reproducibility (SPEED)	0.015 mm
Sensitivity adjustment	Potentiometer or IO-Link
Switching frequency (factory setting)	5.000 Hz (STANDARD)
Switching frequency (STANDARD)	5.000 Hz
Switching frequency (HIGH RESOLUTION)	2.000 Hz
Switching frequency (POWER)	1.000 Hz
Switching frequency (SPEED)	10.000 Hz
Ambient temperature during operation	-25 ... +60 °C
Protection type	IP 67
Connection	Connector, M8, 3-pin
Connection cable	TK ...
More information / accessories	https://www.di-soric.com/211040