



211047
OGUL 121 G3-T3/V4A
Laser fork light barrier

Technical data (typ.)	+20°C, 24 V DC
Laser class	1 (IEC 60825-1)
Color	red
Modulation	Clocked
Fork opening	120 mm
Resolution (factory setting)	0,1 mm (STANDARD)
Reproducibility (factory setting)	0,01 mm (STANDARD)
Resolution (STANDARD)	0,1 mm
Reproducibility (STANDARD)	0,01 mm
Resolution (HIGH RESOLUTION)	0,05 mm
Reproducibility (HIGH RESOLUTION)	0,01 mm
Resolution (POWER)	0,15 mm
Reproducibility (POWER)	0.015 mm
Resolution (SPEED)	0,1 mm
Reproducibility (SPEED)	0.015 mm
Sensitivity adjustment	Potentiometer or IO-Link
Switching frequency (factory setting)	5.000 Hz (STANDARD)
Switching frequency (STANDARD)	5.000 Hz
Switching frequency (HIGH RESOLUTION)	2.000 Hz
Switching frequency (POWER)	1.000 Hz
Switching frequency (SPEED)	10.000 Hz
Ambient temperature during operation	-25 ... +60 °C
Protection type	IP 67
Connection	Connector, M8, 3-pin
Connection cable	TK ...
More information / accessories	https://www.di-soric.com/211047